

MaxLift Manual Chain Hoist

Dedicated to Safety, Efficiency & Economy



Chain hoist are manufactured in accordance with 2006/42/EC Annex I & EN13157 & ANSI/ASME. High Performance Lever hoists engineered for heavy duty industrial service.

Features include:

- Overload protection safety slip clutch device for safer work to use the over load limiter as option
- Rex supplying overload deviced hand wheel only or complete set
- With body
- Corrosion resistant plated hoist body with load chains are optional.
- Grade 80~100 high quality load chain.
- Galvanized hand chain.
- Lightweight compact design.
- Durable powder painting finish.
- Durable pawl springs for additional safety.
- Non asbestos friction disc.
- Long life friction discs.

Optional Items

- Overload protection safety signal device
- Corrosion resistant plated hoist body with load chains
- Spark resistant hoist
- Shipyard hook

Operating Conditions and Environment

Temperature range: -20° to 50°C

Chain Block Specification					
CAP (TON)	MODEL	STD. Lift	LOAD CHAIN DIA (mm) x CHAIN FALL LINES	LOAD CHAIN GRADE	NET WEIGHT (KG)
0.5	MG05	2.5	6.3 x 1	80	11
1	MG10	2.5	6.3 x 1	80	11.5
1.5	MG15	2.5	7.1 x 1	80	13.8
2	MG20	3	7.9 x 1	80	21.6
3	MG30	3	7.1 x 2	80	23
5	MG50	3	9.0 x 2	100	41
7.5	MG75	3.5	9.0 x 3	100	57
10	MG100	3.5	9.0 x 4	100	78
15	MG150	3.5	9.0 x 6	100	150
20	MG200	3.5	9.0 x 8	100	190
30	MG300	3.5	9.0 x 10	100	265
40	MG400	3.5	9.0 x 14	100	472
50	MG500	3.5	9.0 x 16	100	710